

PP RIDGE VENT ROLL



INDEX

1. Code Registry
2. Use
3. Technical Specification

1. CODE REGISTRY

Code	Description	Dimensions (mm)	Weight	Pkg / Pallet
LUC70-9071	PP red ridge vent roll	390 mm x 5 m	1,48 kg/pc.	4 pcs. / 72 pcs.
LUC70-9071M	PP brown ridge vent roll	390 mm x 5 m	1,48 kg/pc.	4 pcs. / 72 pcs.
LUC70-9071N	PP black ridge vent roll	390 mm x 5 m	1,48 kg/pc.	4 pcs. / 72 pcs.

MATERIAL Made of PP (polypropylene) with aluminum flashings.

2. USE

Used to improve ventilation of the ridge.

3. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
Dak.R.LUC70.9071x	Supply and installation of ridge vent roll, central part in PP (polypropylene), heatsealed to the "flashings" on the sides in aluminum or copper. Fabric of central part is UV resistant. Butyl strips on the bottom of flashings in aluminum or copper, make the installation easier ensuring adherence to the brick. Resistant to temperatures between -40° C and 150° C. Made of PP (polypropylene) with aluminum flashings. Used to improve ventilation of the ridge.		
Dak.R.LUC70.9071	red - 390 mm x 5 m.....	pc.	-
Dak.R.LUC70.9071M	brown - 390 mm x 5 m.....	pc.	-
Dak.R.LUC70.9071N	black - 390 mm x 5 m.....	pc.	-