

FOLDING WOOD STAIR



INDEX

1. Code Registry
2. Use
3. Technical Specification

1. CODE REGISTRY

Code	Description	(mm)	Weight	Pkg. / Pallet
SCA04-800	3 pieces of wood folding stair	700 x 1.200 x 2.800	30 kg/pc.	1 pc. / 16 pcs.
SCA04-790	3 pieces of wood folding stair	600 x 1.200 x 2.800	25 kg/pc.	1 pc. / 16 pcs.

MATERIALE

Made of solid wood treated.

2. USE

Usually used in homes to reach attics without the encumbrance of a fixed ladder.
The ladder can be folded up and disappear to make the ceiling indicated in the presence of a confined space.

Step dimensions:

length 33 cm
width 8 cm
thickness 2 cm

3. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
Dak.I.SCA04.xxx	Supply and installation of retractable pine ladder, composed of three hinged elements and a frame with a multilayered trapdoor with a double seal to guarantee an excellent seal (4th class according to EN 12207). The door, white in color, is double layer (sandwich type) for a total thickness of 4.6 cm in order to create an optimal thermal barrier between the room and the attic. The handle ensures greater comfort and safety when using the ladder. Individually packed. Available in the size of the entrance to the attic 700 x 1.200 x 2.800 or 600 x 1.200 x 2.800 mm. Made of solid wood treated. Usually used in homes to reach attics without the encumbrance of a fixed ladder. The ladder can be folded up and disappear to make the ceiling indicated in the presence of a confined space.		
Dak.I.SCA04.800	Dimension 700 x 1.200 x 2.800 mm.....	pc.	-
Dak.I.SCA04.790	Dimension 600 x 1.200 x 2.800 mm.....	pc.	-