

# PVC-ALUMINUM AND COPPER RIDGE VENT ROLL



## INDEX

1. Code Registry
2. Use
3. Technical Specification

## 1. CODE REGISTRY

Code	Description	Dimensions (mm)	Weight	Pkg / Pallet
LUC70-9070A	PVC-Aluminum red ridge vent roll	390 mm x 5 m	1,48 kg/pc.	4 pcs. / 72 pcs.
LUC70-9070AN	PVC-Aluminum black ridge vent roll	390 mm x 5 m	1,48 kg/pc.	4 pcs. / 72 pcs.
LUC70-9070R	PVC-Copper red ridge vent roll	360 mm x 5 m	1,48 kg/pc.	4 pcs. / 72 pcs.

### MATERIAL

Made of PVC with aluminum or copper flashings.

## 2. USE

Used to improve ventilation of the ridge.

## 3. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
<b>Dak.R.LUC70.9070x</b>	Supply and installation of ridge vent roll, central part in PVC, heat-sealed to the "flashings" on the sides in aluminum or copper. PVC ensures excellent resistance to heat and UV rays. Butyl strips on the bottom of flashings in aluminum or copper, make the installation easier ensuring better adherence to the brick. Resistant to temperatures between -40° C and 150° C. Made of PVC with aluminum or copper flashings. Used to improve ventilation of the ridge.		
<b>Dak.R.LUC70.9070A</b>	390 mm x 5 m.....	pc.	-
<b>Dak.R.LUC70.9070AN</b>	390 mm x 5 m.....	pc.	-
<b>Dak.R.LUC70.9070R</b>	360 mm x 5 m.....	pc.	-