

JUNCTION G125



INDEX

1. Code registry
2. Description
3. Features
4. Technical specification

1. CODE REGISTRY

Code	Description	Measure (m)	Weight	Colour	Pkg / Pallet
GRO03-3215M	Junction	h 115 - l 153 - p 90	1,42 kg/pz.	Brown	1 pc. / 48 boxes
GRO03-3215R	Junction	h 115 - l 153 - p 90	1,42 kg/pz.	Copper effect	1 pc. / 48 boxes

MATERIAL Made of PVC U.V. ray resistant

2. DESCRIPTION

The junctions are necessary for the connection of gutter channels

JUNCTION G125

3. FEATURES

GENERAL FEATURES		Requirements		
Material	PVC			
Colour	CIELAB L, a, b	GRO03-3200MUN brown	GRO03-3200RUN copper effect	EN 607
ΔE		Max 2,00		

DIMENSIONAL DATA	Unit	Value		without gasket
		GRO01-3115M Brown	GRO01-3115R Copper effect	
h	mm	115		
l	mm	153		
p	mm	90		
QUOTE				

FISICAL AND MECHANICAL FEATURES	Test conditions	Value	Method
Heat reversion	65° C 30 min. in air	NO DEFORMATION	EN ISO 607
VICAT point (VST)	50° C/h 50 N	≥ 75° C	EN ISO 2507

4. TECHNICAL SPECIFICATION

Code	Description	Unit	Price
Dak.R.GRO03.3200xxx	Supply and installation of junction for gutter channels In the measurements of h 115 - l 153 - p 90 mm Made of PVC resistant to U.V rays. Use for the collection of meteoric waters from the covers and relative disposal.		
Dak.R.GRO03.3200MUN	Brown.....	cf.	-
Dak.R.GRO03.3200RUN	Copper effects.....	cf.	-