

n: TER11-3110AV

SGR-AV ANCHOR (STEEL SCREW) Ø 8 mm



1. Unique identification code of the product-type:

TER11-3110AV

SGR-AV ANCHOR (Steel Screw) 8 mm - length. 110

TER11-3130AV

SGR-AV ANCHOR (Steel Screw) 8 mm - length. 130

TER11-3150AV

SGR-AV ANCHOR (Steel Screw) 8 mm - length. 150

TER11-3170AV

SGR-AV ANCHOR (Steel Screw) 8 mm - length. 170

TER11-3190AV

SGR-AV ANCHOR (Steel Screw) 8 mm - length. 190

TER11-3210AV

SGR-AV ANCHOR (Steel Screw) 8 mm - length. 210

TER11-3230AV

SGR-AV ANCHOR (Steel Screw) 8 mm - length. 230

TER11-3250AV

SGR-AV ANCHOR (Steel Screw) 8 mm - length. 250

TER11-3270AV

SGR-AV ANCHOR (Steel Screw) 8 mm - length. 270

TER11-3290AV

SGR-AV ANCHOR (Steel Screw) 8 mm - length. 290

TER11-3310AV

SGR-AV ANCHOR (Steel Screw) 8 mm - length. 310

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

THE BATCH NUMBER IS PRINTED ON THE PACKAGE ADD ITS SINGLE PRODUCT.

3. Uso previsto dal prodotto da costruzione, conformemente alla relativa specifica tecnica armonizzata, come previsto dal fabbricante:

PLASTIC ANCHORS FOR FIXING OF EXTERNAL THERMAL INSULATION COMPOSITE SYSTEMS WITH RENDERING IN CONCRETE AND MASONRY

4. Name, registered trade name or registered trade mark and contact address of the manufacturer in the production factory:

DAKOTA GROUP SAS
Via Pitagora 3
37010 Affi (VERONA) - ITALY

5. System or systems of assessment and verification of constancy of performance of the construction product:

SYSTEM 2+

6. Notified Body TZUS, TECHNICAL AND TEST INSTITUTE FOR CONSTRUCTION PRAGUE, number 1020, released the ETA 17/0606 based on EAD 330196-01-0604, issuing the CPR-090-046242 factory production control certificate.

7. Declared Performance

N _{RK} Base materials	kN	Technical Specification
Cat. A Concrete - C 12/15 (EN 206-1) - C 16/20-C50/60 (EN 206-1)	0,40 0,60	pt. 5.4.2 ETAG 014
Cat. B Solid clay bricks (EN 771-1)	0,60	pt. 5.4.2 ETAG 014
Cat. C Vertically perforated clay bricks (EN 771-1)	0,50	pt. 5.4.2 ETAG 014
Cat. D Lightweight aggregate concrete hollow blocks (EN 1520)	0,50	pt. 5.4.2 ETAG 014
Cat. E Autoclaved aerated concrete AAC 4 (EN 771-4)	0,30	pt. 5.4.2 ETAG 014

N_{RK} Characteristic resistance to load

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Zeno Cipriani - Legal Representative
Dakota Group S.a.S.



(Signature)

Brentino Belluno - 02-12-2019

(Place and Date)