

FIBER GLASS MESH FOR SKIM COATING (90 GR - R72)



INDEX

1. Code Registry
2. Use
3. Technical specification

1. CODE REGISTRY

Code	Description	Dimensions (m)	Weight	Colour	Pkg. / Pallet
RET01-1010	Fiber glass mesh for thin skim coating - R72	1,00 x 50 m	90 gr./m ²	White	50 m ² / 2.250 m ²

MATERIAL

Made of fiber glass Adfors Saint-Gobain type E, impregnated with anti-alkaline resins SBR, mesh 3,2 x 3,2 mm and weight of 90 gr/m².

Characteristics	Units Description	RET01-1010	
		Warp	Weft
Setting	per 10 cm	28 x 2	25
Weight (Tex)	gr/1000 m	68	136
Standard height	cm	100	
Roll length	m	50	
Treated Fabric Thickness	mm	0,32	
Loom state Fabric Weight	g/m ²	72	
Treated Fabric Weight	min g/m ²	90	
Combustible Matter Content (LOI)	% of mass	18	
Treatment type		Alkali resistant without emollient	
Square Dimension	mm	3,2 x 3,2	

Tensile strength (TS) and elongation:

Minimum individual tensile strength (N/50 mm) and maximum elongation (%) when reaching minimum tensile strength is ascertained according DIN EN ISO 13934 - 1 as per below.

Deposition method	Tensile strength		Elongation
	Nominal value	Individual value	Average value
Standard condition	800 / 750	800 / 700	3,5 / 3,5
5 % NaOH Solution	250 / 350	235 / 250	3,5 / 3,5
Fast Test	1.200 / 1.200	400 / 350	4,0 / 4,0

Tolerances:

Setting: ± 5% in Warp and Weft
Width: ± 1%
Length: ± 2%
LOI: ± 3%

Quality Inspection:

Quality inspection, sampling and material acceptance follows the Customer Acceptance Standard No. 0326.

Packing:

The rolls of fabrics are packed vertically in a cardboard box, on a wooden pallet.

A precise method of packing is mentioned in the works standard for packing and can vary based on a customer request.

Storing:

Packed rolls are to be stored in dry rooms. Storing temperature is from -10 °C to +50°C.

2. USE

Used in the mesh layer of plaster to avoid cracking in the presence of gypsum nichings and to reinforce joints between different materials.

Fiber glass mesh with an higher tensile strength than the R58 mesh (Art. RET01-1000).

With high wettability and adaptability to all the products that are on the market.

FIBER GLASS MESH FOR SKIM COATING (90 GR - R72)

3. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
Dak.B.RET01.1010	<p>Supply and installation of White fiber glass mesh (identification code R72, corresponding to net weight per square meter of fiber glass mesh without resin). Height available 1,00 x 50 m. Packed in cellophane rolls.</p> <p>Made of fiber glass Adfors Saint-Gobain type E, impregnated with anti- alkaline resins SBR, mesh 3,2 x 3,2 mm and weight of 90 gr/m². Used in the finish layer of plaster to avoid cracking in the presence of gypsum finishings and to reinforce joints between different materials. Fiber glass mesh with an higher tensile strength than the R58 mesh (Art. RET01-1000). With high wettability and adaptability to all the products that are on the market. Dimensions 1,00 x 50 m.....</p>	m ²	-