

BRIDGE SHAPED SPACER FOR FORMWORK



INDEX

1. Code Registry
2. Use
3. Technical Specification

1. CODE REGISTRY

Code	Description	Dimension (mm)	Weight	Pkg. / Pallet
PRO12-1215N	Bridge shaped spacer for formwork	h 15 l=2.000	11,50 kg/box	100 m / 42 boxes
PRO12-1220N	Bridge shaped spacer for formwork	h 20 l=2.000	13,00 kg/box	100 m / 63 boxes
PRO12-1225N	Bridge shaped spacer for formwork	h 25 l=2.000	15,00 kg/box	100 m / 49 boxes
PRO12-1230N	Bridge shaped spacer for formwork	h 30 l=2.000	16,40 kg/box	100 m / 42 boxes
PRO12-1235N	Bridge shaped spacer for formwork	h 35 l=2.000	11,52 kg/box	60 m / 60 boxes
PRO12-1240N	Bridge shaped spacer for formwork	h 40 l=2.000	11,40 kg/box	60 m / 40 boxes
PRO12-1250NN	Bridge shaped spacer for formwork	h 50 l=2.000	8,90 kg/box	60 m / 28 boxes

MATERIAL

Made of thermoset plastic.

2. USE

Specific use in construction.

It keeps the formwork at same distance (in vertical way) during the pour of concrete.

3. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
Dak.O.PRO12.12xxN	Supply and installation of bridge shaped spacer for formwork allows installation in bridge formwork. Made of thermoset plastic. Specific use in construction. It keeps the formwork at same distance (in vertical way) during the pour of concrete.		
Dak.O.PRO12.1215N	h 15 l = 2.000 mm.....	pcs	-
Dak.O.PRO12.1220N	h 20 l = 2.000 mm.....	pcs	-
Dak.O.PRO12.1225N	h 25 l = 2.000 mm.....	pcs	-
Dak.O.PRO12.1230N	h 30 l = 2.000 mm.....	pcs	-
Dak.O.PRO12.1235N	h 35 l = 2.000 mm.....	pcs	-
Dak.O.PRO12.1240N	h 40 l = 2.000 mm.....	pcs	-
Dak.O.PRO12.1250NN	h 50 l = 2.000 mm.....	pcs	-