

# BEND 45° Ø 80



## INDEX

1. Code registry
2. Description
3. Features
4. Technical specification

## 1. CODE REGISTRY

Code	Description	Dimensions (mm)	Spigot (mm)	Socket (mm)	Weight (kg)	Colour	Pkg / Pallet
GRO03-3260M	Bend 45° Ø 80	h 144 - l 118 - p 85	1,50	1,40	0,808	Brown	8 pc. / 48 boxes
GRO03-3260R	Bend 45° Ø 80	h 144 - l 118 - p 85	1,50	1,40	0,808	Copper effect	8 pc. / 48 boxes

**MATERIAL** Made of PVC U.V. ray resistant

## 2. DESCRIPTION

The 45° bend for Ø 80 rain pipes, allows the junction with the rainways and allows direction changes for the correct water outflow

# BEND 45° Ø 80

## 3. FEATURES

GENERAL FEATURES	Requirements			
Material	PVC			
Colour	CIELAB L, a, b	GRO03-3260M brown	GRO03-3260R copper effect	EN 12200

DIMENSIONAL DATA		Unit	Value		without gasket
			GRO03-3260M Brown	GRO03-3260R Copper effect	
Min. thicknesses	Spigot	mm	1,50		
	Socket	mm	1,40		
Dimensions	h	mm	144,00		
	l	mm	118,00		
	p	mm	85,00		
QUOTE					

FISICAL AND MECHANICAL FEATURES	Test conditions	Value	Method
Temperature VICAT (VST)	50° C/h 50 N	≥ 75° C	EN ISO 2507

## 4. TECHNICAL SPECIFICATION

Code	Description	Unit	Price
<b>Dak.R.GRO03.3260x</b>	Supply and installation of a 45° Ø 80 curve to combine rain pipes Dimensions: h 144 - l 118 - p 85 mm, spigot 1,50 mm, socket 1,40 mm Made of PVC resistant to U.V rays. Used to connect two rain pipes and redirect the water flow at the desired point		
<b>Dak.R.GRO03.32560M</b>	Brown.....	pc	-
<b>Dak.R.GRO03.3260R</b>	Copper effect.....	pc	-