

T CONNECTION 87° Ø 80



INDEX

1. Code registry
2. Description
3. Features
4. Technical specification

1. CODE REGISTRY

Code	Description	Dimensions (mm)	Spigot (mm)	Socket (mm)	Weight (kg)	Colour	Pkg / Pallet
GRO03-3280M	T connection 87° Ø 80	h 179 - l 130 - p 85	1,50	1,40	0,83	Brown	5 pc. / 48 boxes
GRO03-3280R	T connection 87° Ø 80	h 179 - l 130 - p 85	1,50	1,40	0,83	Copper effect	5 pc. / 48 boxes

MATERIAL Made of PVC U.V. ray resistant

2. DESCRIPTION

The T connection has the function of junction between two rain pipes

T CONNECTION 87° Ø 80

3. FEATURES

GENERAL FEATURES	Requirements			
Material	PVC			
Colour	CIELAB L, a, b	GRO03-3280M brown	GRO03-3280R copper effect	EN 12200

DIMENSIONAL DATA		Unit	Value		without gasket
			GRO03-3280M Brown	GRO03-3280R Copper effect	
Min. thicknesses	Spigot	mm	1,50		
	Socket	mm	1,40		
Dimensions	h	mm	210,00		
	l	mm	175,00		
	p	mm	85,00		
QUOTE					

FISICAL AND MECHANICAL FEATURES	Test conditions	Value	Method
Temperatura VICAT (VST)	50° C/h 50 N	≥ 75° C	EN ISO 2507

4. TECHNICAL SPECIFICATION

Code	Description	Unit	Price
Dak.R.GRO03.3280x	Supply and installation of connection T 87° Ø 80 Dimensions: h 179 - l 130 - p 85 mm, spigot 1,50 mm, socket 1,40 mm Made of PVC resistant to U.V rays. Used for connecting two rain pipes		
Dak.R.GRO03.3280M	Brown.....	pc.	-
Dak.R.GRO03.3280R	Copper effect.....	pc.	-