

DK TAPE S-CRACKSTOP



INDEX

1. Code Registry
2. Use
3. Technical Specification

1. CODE REGISTRY

Code	Product Description	Dimensions (m)	Weight	Colour	Pkg. / Pallet
RET03-4050	Dk Tape S-Crackstop	1,00 x 25 m	70 gr./m ²	White	25 m ² / 2.400 m ²

MATERIAL Made of fiber glass Adfors Saint-Gobain.

Characteristics	Units Description	RET03-4050	
		Warp	Weft
Setting	per 10 cm	35,4	35,4
Standard height	cm	100	
Roll length	m	25	
Treated Fabric Thickness	mm	0,26	
Loom state Fabric Weight	g/m ²	70	
DPU	%	41 - 47	

Tolerances:

Height: ± 1%
 Length: ± 2%
 LOI: ± 3%

Packing:

The rolls of fabrics are packed vertically in a cardboard box, on a wooden pallet.

Storing:

Packed rolls are to be stored in dry rooms. Storing temperature is from -10 °C to +50°C.

2. USE

Used on interior walls or drywall, to repair cracks that may occur around windows or doors and in the restoration of damaged plaster or finishing panels and block walls. Self-adhesive.

3. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
Dak.B.RET03.4050	Supply and installation of White fiber glass mesh. Recommended for the restoration of damaged walls, due to cracks and fissures, this self-adhesive mesh is easy to install, ideal for interior walls and ceilings. Once attached to the surface, it only requires a thin grout, size h. 1,00 x 25 m. Packed in cellophane rolls. Made of fiber glass Adfors Saint-Gobain. Used on interior walls or drywall, to repair cracks that may occur around windows or doors and in the restoration of damaged plaster or finishing panels and block walls. Self-adhesive.	m ²	-