

STEEL CORE DRILLING SET VARIABLE DEPTH & CORE DRILLING ø 70 mm



INDEX

1. Code Registry
2. Use
3. Technical specification

1. CODE REGISTRY

Code	Description	Dimensions (mm)	Weight	Colour	Pkg. / Pallet
ZIN35-1760	Steel Core drilling set variabile depth (ø 8 mm and ø 10 mm)	ø 70	0,500 kg/pc.	-	1 pc. / - pc.
TER11-2310	Core drilling ø 70 mm	ø 70	0,100 kg/pc.	-	100 pcs. / 3.000 pcs.

MATERIAL Made of hardened steel

2. USE

Used to create a suitable cavity in the insulation board for the installation of dowels and subsequent covering with insulation material caps (EPS, Graphite, Rock Wool)
Suitable for any insulation board.

3. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
Dak.B.x	Supply of Core drill with cutter completed with two drill bits (ø 8 mm and ø 10 mm). Packed in a kit. Core drill grey colour. Packed in cellophane. Made of hardened steel. Used to make holes in the insulations system panels (holes diameter 70 mm). Suitable for all materials, especially for rock wool.		
Dak.B.ZIN35.1760	Hardened Steel.....	pc.	-
Dak.B.TER11.2310	Polyamide.....	pc.	-