

# LOWERED SIPHONED GULLY 150 x 150



## INDEX

1. Code Registry
2. Use
3. Technical Specification

## 1. CODE REGISTRY

Code	Description	Dimensions (mm)	Weight	Pkg. / Pallet
TER07-1342	Lowered Siphoned Gully (ABS grating)	150 x 150	0,120 kg/pc.	25 pcs / 500 pcs
TER07-1342I	Lowered Siphoned Gully (Stainless Steel grating)	150 x 150	0,120 kg/pc.	25 pcs / 500 pcs

**MATERIAL** Made of ABS

## 2. USE

Used for drainage of rain water on the terraces, or on screeds little shimmed and/or where the slope does not allow the "elbow" attack to the outlet.

## 3. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
<b>Dak.D.TER07.1342x</b>	Supply and installation of ABS adjustable gully, with stainless steel AISI 304 BA or ABS gratings, with size of 150 x 150 mm, packed in blister. The lowered bottom outlet can be oriented and rotated up to 360 degrees. The internal outlet dimension is 45 mm, the external one is 50 mm. Made of ABS. Used for drainage of rain water on the terraces, or on screeds little shimmed and/or where the slope does not allow the "elbow" attack to the outlet.		
<b>Dak.D.TER07.1342</b>	ABS grating.....	pc.	-
<b>Dak.D.TER07.1342I</b>	Stainless Steel grating.....	pc.	-