

HOOK WITH CURVED SPRING FOR CEILING PROFILE 27/60



INDEX

- 1. Code registry
- 2. Description
- 3. Use
- 4. Features
- 5. Technical specification

1. CODE REGISTRY

Code	Description	Dimension (mm)	Weight	Colour	Pkg. / Pallet
GAN01-5123E	Hook with curved sprong for ceiling profile 27/60	27 x 60	0,039 kg/pc.	Gray	100 pcs. / 37.800 pcs.

MATERIAL Laminated sheet metal DX51.

2. DESCRIPTION

The curved spring clip hook is a metal construction element used for quick mounting of metal profiles. It is produced by compression molding from a galvanized metal sheet with a thickness of 1.00 mm and equipped with a single spring clip attached to the hook with two rivets. the hook is also available without a spring clip for direct mounting on wooden structures or movable steel belts.

3. USE

The product is used for mounting DA 60 x 27 metal profiles in horizontal building constructions. This hook is ideal for installation of suspended ceilings and other suspended interior structures, offering a versatile and reliable solution for secure anchoring in a variety of construction contexts, such as commercial, industrial, and residential buildings. The hook's curved design allows for even weight distribution and better adaptability to various mounting configurations.

4. FEATURES

Material	Laminated sheet metal DX51	
Coating	Zinc - min Z100	EN 10327
Body thickness	1,00 mm	EN 10143
Spring thickness	20 mm	EN 10143
Spring width	0,8 mm	
Load	0,40 kN	
Reaction to fire	A1 Class	EN 14195
Durability	B Class	
Box	100 pcs	

HOOK WITH CURVED SPRING FOR CEILING PROFILE 27/60

5. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
Dak.B.GAN01.5123E	Supply and installation of Hook with spring for ceiling profile 27/60 mm. Packaged in boxes of 100 pcs. Made of galvanized steel sheet. Used for installation of suspended ceilings and other suspended interior structures.	pkg	-