

DIFU STOP ALU 1500



INDEX

1. Code Registry
2. Use
3. Technical Specification

1. CODE REGISTRY

Code	Description	Dimensions (m)	Weight	Colour	Pkg. / Pallet
LUC70-9097	Difu Stop Alu 1500	1,50 x 50	130 gr/m ²	Aluminum	75 m ² / 30 rolls

MATERIAL Made of PE (polyethylene) and aluminum.

PROPERTIES	REFERENCE STANDARD	UNITY	Difu Stop Alu 120
TENSILE STRENGTH MD/CD:	EN 12311-1	[N/5cm MD/CD]	480 / 480
RESISTANCE TO TEARING (NAIL SHANK) MD/CD:	EN 12311-1	N/20cm MD/CD]	100 / 100
RESISTANCE TO TEMPERATURES		°C (min. / max.)	-30 / +80
VALUE S _D	EN ISO 12572	m	> 100
UV RESISTANCE (NOT COVERED)		month	1

2. USE

It is used to prevent the passage of vapour.
It is suggested in areas subjected to variable humidity.

3. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
Dak.R.LUC70.9097	Supply and installation of Vapour barrier. It is composed of 1 layer in aluminum and 2 layers in polyethylene. Rolls = 1,50 x 50 m. Single packed in cellophane tape. Made of PE (polyethylene) and aluminum. It is used to prevent the passage of vapour. It is suggested in areas subjected to variable humidity.	roll.	-