#### DAKOTA<sup>TECHNICAL DATA SHEET</sup> Rev: 17 January, 2023

## **PROTECTIVE TAPE FOR JOIST**



#### INDEX

- 1. Code registry
- 2. Use
- 3. Description
- 4. Features
- 5. Technical specification

#### **1. CODE REGISTRY**

Code	Description	Measure (mm)	Weight (kg)	Pkg / Pallet
TER09-1188	Protective tape for joist	80 x 20.000 th. 2	0,32	27 pcs / 256 pcs

MATERIAL Made of stretch polyethylene

#### 2. USE

Used to protect the joist and waterproof the overall structure.

### **3. DESCRIPTION**

Single-sided adhesive tape for fixing and protecting joists, before the installation of decking boards.





# **PROTECTIVE TAPE FOR JOIST**

#### **4. FEATURES**

CHARACTERISTICS (dimensional tolerances ±15%)	TEST METHOD	VALUE
THICKNESS	Internal	3,5 -2 mm
DENSITY	Internal	30 g/cm <sup>3</sup>
STANDARD COLORS		DARK GRAY MATTE
ACUSTICAL IMPROVEMENT OF THE PRO- DUCT ONLY RW ACCORDING TO RESEARCH DATA IN OUR POSSESSION.	UNI EN ISO 10140-3:2010	2 dB
DYNAMIC RIGIDITY	UNI EN 29052-1:1993	45 MN/m <sup>3</sup>
THERMAL CONDUCTIVITY	EN 12667 AVERAGE VALUE BASED ON LABORATORY CERTIFICATES AND DATA IN OUR POSSESSION	0,040 W/mK A 10° C
TEMPERATURE OF USE		-20 +80° C
VERTICAL COMPRESSION RESISTANCE KPa FOR SP- 3.5 mm	UNI EN ISO 7214:2008	SEE TABLE BELOW
RESISTANCE TO MOLD AND INSECTS		EXCELLENT
DOES NOT CONTAIN CFC (FREON)		IN ACCORDANCE WITH ITALIAN LAW NO. 549 OF 12/28/93
ADHESIVE		HOT MELT
ADHESIVE COVER		PLASTIC FILM
COMPRESSIVE STRENGTH		
MASS PER EACH m <sup>2</sup> OF SURFACE (Kg/m <sup>2</sup> )	PRESSURE EXERCITED BY THE BASE ON THE SLAB (KPa)	CRUSHING SUFFERED BY THE THICKNESS. 3,5 (mm)
140	1.373	0,3
210	2.060	0,5
300	2.943	0,7



#### **5. TECHNICAL SPECIFICATION**

Item	Description	Unit	Price
Dak. D. TER 09. 1188	Supply and installation of protective tape for joist Made of stretch polyethylene Used for the protection of joist for floor	pc.	-



This data sheet supersedes and replaces all previous ones. The information contained herein is accurate to our present knowledge. Dakota Group S.a.S. assumes no responsibility or liability with respect to the information given. Dakota Group S.a.S. reserves the right to change speci cations and models without prior notice. Dakota Group S.a.S. - Via Don Cesare Scala, 55 - Brentino Belluno (VR) - Italy - tel. 045-6284080 - fax. 045-6284075 www.dakota.eu - info@dakota.eu o u cio.tecnico@dakota.eu

pag. 2/2