

ANTI-NOISE RUBBER SHIM



TER9-1123R



TER9-1143/G



TER9-1147/G

INDEX

1. Code registry
2. Description
3. Use
4. Laying tips
5. Technical specification

1. CODE REGISTRY

Cose	Description	Measures (mm)	Weight	Pkg. / Pallet
TER09-1123/G	Anti-noise rubber 3mm thickness	Ø 110 - thickness 3	-	600 pc. / 5.400 pcs.
TER09-1143/G	Anti-noise rubber for Arkimede™	Ø 120 - thickness 2	0,04 kg/pc.	180 pc. / 8.100 pcs.
TER09-1147/G	Anti-noise rubber for Arkimede™ 10	Ø 157 - thickness 1	0,03 kg/pc.	120 pc. / 15.120 pcs.

MATERIAL TER09-1143/G e TER09-1147/G made of thermoplastic rubber (TPE). TER09-1123R made of rubber (EPDM)

2. DESCRIPTION

Anti-noise rubber for use in conjunction with Arkimede™ adjustable supports

- Model TER09-1143/G is compatible with Arkimede™ 18, 35, 41, 60 and 115 in **Paving version only**.
- Model TER09-1147/G is compatible **only for Arkimede™ 10** both Paving and Decking. it is also compatible with the fixed support TER09-1120.
- Model TER09-1123R is compatible with all Arkimede™ models (**except** Arkimede™ 10) for Paving and 3D-Scopic.

TER09-1147/G To be placed on terminal Support Arkimede 10 Decking (TER09-1147/1A), Arkimede 10 Paving (TER09-1147/4A2M and TER09-1147/4A4M) and Fixed Support for Quadrotti (TER09-1120)

3. USE

Applied to the head of Arkimedes™ supports, they provide greater friction between the tile (also magatel for those compatible with Arkimedes™ 10) and the support resulting in reduced footfall noise

4. TECHNICAL SPECIFICATION

Item	Description	Unit	Price
Dak.O.TER09-11xx/x	Supply and installation of anti-noise rubber with the following characteristics: · Model TER09-1143/G is compatible with Arkimede™ 18, 35, 41, 60 and 115 in Paving version only. · Model TER09-1147/G is compatible only for Arkimede™ 10 both Paving and Decking. it is also compatible with the fixed support TER09-1120. · Model TER09-1123R is compatible with all Arkimede™ models (except Arkimede™ 10) for Paving and 3D-Scopic. High capacity > 300 ton/m2. Made of PE-HD (high-density polyethylene). For reinforcing and consolidating grass surfaces intended for car parking and/or play activities and/or outfitting.		
Dak.O.TER09-1123R	Measures Ø 110 - thickness 3 mm	pc.	-
Dak.O.TER09-1143/G	Measures Ø 120 - thickness 2 mm	cf.	-
Dak.O.TER09-1147/G	Measures Ø 110 - Ø 157 - thickness.....	cf.	-