

# ANTI-NOISE RUBBER MAT



## INDEX

- 1. Code Registry
- 2. Use
- 3. Installation
- 4. Technical Specification
- 5. Storage

## 1. CODE REGISTRY

Code	Description	Dimension (mm)	Weight	Pkg. / Pallet
TER09-1144	Anti-noise rubber mat	200 x 200 - thick. 3	0,09 kg/pcs	80 pcs / 6.720 pcs

**MATERIAL** Made of rubber (TPV).

## 2. USE

Used to be positioned at the base of the ARKIMEDE range telescopic support to reduce footfall noise up to 12 dB.

## 3. INSTALLATION

- Clean the surface to be insulated, removing any unevenness present.
- Spread the mat with the smooth surface facing upwards.
- Place a protective film in polyethylene or similar and proceed with the laying of the flooring laying screed.

## 4. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
<b>Dak.D. TER09-1144</b>	Supply and installation of Sound absorbing rubber mat for Arkimede range telescopic support. Thickness 3 mm. Made of rubber (TPV). Used to be positioned at the base of the ARKIMEDE range telescopic support to reduce footfall noise up to 12 dB.	pcs	-

## 5. STORAGE

Store away from direct sunlight.