

ANTI-NOISE RUBBER MAT



INDEX

- 1. Code Registry
- 2. Use
- 3. Installation
- 4. Technical Specification
- 5. Storage

1. CODE REGISTRY

Code	Description	Dimension (mm)	Weight	Pkg. / Pallet
TER09-1144	Anti-noise rubber mat	200 x 200 - thick. 3	0,09 kg/pcs	80 pcs / 6.720 pcs

MATERIAL Made of rubber (TPV).

2. USE

Used to be positioned at the base of the ARKIMEDE range telescopic support to reduce footfall noise up to 28 dB (testing on hollow masonry slab), in accordance with UNI EN ISO 10140 ex 140/6.

3. INSTALLATION

- Clean the surface to be insulated, removing any unevenness present.
- Spread the mat with the smooth surface facing upwards.
- Place a protective film in polyethylene or similar and proceed with the laying of the flooring laying screed.

4. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
Dak.D. TER09-1144	Supply and installation of Sound absorbing rubber mat for Arkimede range telescopic support. Thickness 3 mm. Made of rubber (TPV). Used to be positioned at the base of the ARKIMEDE range telescopic support to reduce footfall noise up to 12 dB.	pcs	-

5. STORAGE

Store away from direct sunlight.