DAKOTA TECHNICAL DATA SHEET

STILTS



INDEX

- 1. Code registry
- 2. Description
- 3. Use
- 4. Technical specification

1. CODE REGISTRY

| Code | Description | Measures (mm) | Weight | Color | Pkg. / Pallet |
|------------|-------------|-----------------|--------|----------|---------------|
| TER23-5414 | Stilts | from 457 to 762 | - | Aluminum | 1 pc. / - |

MATERIAL Aluminum, plastic and fabric

2. DESCRIPTION

Stilts with heights from 457 to 762 mm

Main features

- Natural motion
- Made of high-quality aluminum
- Leg supports with cushioned pads to provide great comfort
- Metal buckles to ensure secure fastening
- Adjustable support for different foot sizes
- Knurled-head screws for tool-free adjustment of the feet
 Double-action springs for added flexibilitySlip-resistant soles
- Double-action springs for added flexibilitysi
 Maximum load capacity: 102kg
- Maximum load capacity: I
 All parts are available
- CE certified

3. USE

They are used to carry out assembly or grouting work without resorting to the use of ladders or scaffolding.

4. TECHNICAL SPECIFICATION

| ltem | Description | U.M. | Price |
|------------------|--|------|-------|
| Dak.B.TER23-5414 | Stilts with heights from 457 to 762 mm used to carry out assembly or grouting work without resorting to the use of ladders or scaffolding. Made of steel, plastic and fabric | pc. | - |



