

CIRCULAR SPACER



INDEX

1. Data and Documentation
2. Use
3. Specifications

1. DATA AND DOCUMENTATION

Code	Description	Dimensions (mm)	Weight	Pkg. / Pallet
PRO12-1658	Circular Spacer	h. dist. 10 Ø 4/8	0.004 kg/pc.	2,000 pcs. / 30,000 pcs.
PRO12-1658B	Circular Spacer	h. dist. 15 Ø 4/8	0.005 kg/pc.	1,800 pcs / 27,000 pcs.
PRO12-1659	Circular Spacer	h. dist. 20 Ø 4/8	0.005 kg/pc.	1,500 pcs. / 22,500 pcs.
PRO12-1659B	Circular Spacer	h. dist. 25 Ø 4/12	0.006 kg/pc.	1,500 pcs. / 22,500 pcs.
PRO12-1657	Circular Spacer	h. dist. 30 Ø 4/12	0.006 kg/pc.	1,000 pcs. / 15,000 pcs.
PRO12-1657B	Circular Spacer	h. dist. 40 Ø 6/14	0.009 kg/pc.	500 pcs. / 22,500 pcs.

MATERIAL

Made of thermosetting plastic.

2. USE

Specific use in construction.

It allows the installation of steel reinforcements while maintaining the correct spacing for the 'iron cover'.

3. SPECIFICATION ITEMS

Entry	Description	Unit	Price
Dak.O.PRO12.165x	Supply and installation of bridge spacer its circular shape allows for the installation of reinforcement cages. Packaged in a box. Made of thermosetting plastic. Specific use in construction. It allows the installation of steel reinforcements while maintaining the correct spacing for the 'iron cover'.		
Dak.O.PRO12.1658	Dimensions h. dist. 10 mm.....	pc.	-
Dak.O.PRO12.1658B	Dimensions h. dist. 15 mm.....	pc.	-
Dak.O.PRO12.1659	Dimensions h. dist. 20 mm.....	pc.	-
Dak.O.PRO12.1659B	Dimensions h. dist. 25 mm.....	pc.	-
Dak.O.PRO12.1657B	Dimensions h. dist. 30 mm.....	pc.	-
Dak.O.PRO12.1668	Dimensions h. dist. 40 mm.....	pc.	-