

# DK PLASTER S-VEIL TAPE



## INDEX

1. Data and Documentation
2. Use
3. Specifications

## 1. DATA AND DOCUMENTATION

Code	Description	Measurements (m)	Weight	Colour	Pkg. / Pallet
RET03-VEL240/25	Dk Plaster S-Veil tape	h. 5 cm x 25	45 g/m <sup>2</sup>	White	48 pcs. / 1,248 pcs.

**MATERIAL** Adfors Saint-Gobain fibreglass mesh.

Features	Units of Measurement	RET03-VEL240	
		Warp	Plot
Tensile strength	N/2.45 cm	75 N	43 N
Standard Height	cm	100	
Roll length	m	15	
Thickness Treated Fabric	mm	0,39 ± 4	
Raw Fabric Weight	g/m <sup>2</sup>	45 ± 4	
Fuel Content (LOI)	% mass	18 - 22	

**Tolerances:**

Height: ± 1%  
Length: ± 2%  
LOI: ± 3%

**Packing:**

The rolls are packed vertically in cardboard boxes on a pallet. Warehouse:  
Rolls must be stored in a dry place. Storage temperature -10 °C to + 50 °C.

## 2. USE

Used on interior walls or plasterboard.  
Smooth out irregularities and stabilise plaster and plasterboard compound.  
Restore damaged plaster or finishing panels.

## 3. SPECIFICATION ITEMS

Entry	Description	U.M.	Price
Dak.B.RET03.VEL240/25	Supply and installation of Tape as an alternative to netting h. 5 cm x 25 m, for point applications on joints. Packed in boxes. Made of Adfors Saint-Gobain fibreglass. Used on interior walls or plasterboard. Smooth out irregularities and stabilise plaster and plasterboard compound. Restore damaged plaster or finishing panels. Dimensions 1.00 x 15 m.....	m <sup>2</sup>	-