

SELF-ADHESIVE BUTYL TAPE



INDEX

1. Data and Documentation
2. Use
3. Specifications

1. DATA AND DOCUMENTATION

Code	Description	Dimensions (mm)	Weight	Pkg / Pallet
LUC70-9215S	Self-Adhesive Butyl Tape	150 x 10 m	10.00 kg/ff.	4 pcs. / - cf.
LUC70-9222S	Self-Adhesive Butyl Tape	225 x 10 m	9.40 kg/cf.	4 pcs. / - cf.

MATERIAL

Made of a butyl rubber compound coated on a PP (polypropylene) fleece.

2. USE

Used for waterproofing and finishing between attic window and membrane, for indoor applications where effective adhesion to materials such as concrete, plasterboard or marble is required.

It also provides a finished, rough and absorbent solution. Also ideal for laying wood, marble and terracotta floor coverings.

3. SPECIFICATION ITEMS

Entry	Description	Unit	Price
Dak.R.LUC70.92xxS	Supply and installation of self-adhesive sealing tape. Made of a butyl rubber compound coated on a PP (polypropylene) fleece. Used for waterproofing and finishing between attic window and membrane, for indoor applications where effective adhesion to materials such as concrete, plasterboard or marble is required. It also provides a finished, rough and absorbent solution. Also ideal for laying wood, marble and terracotta floor coverings.		
Dak.R.LUC70.9215S	Size 150 mm.....	pc.	-
Dak.R.LUC70.9222S	Size 225 mm.....	pc.	-