

INSPECTION HATCH



INDEX

1. Data and Documentation
2. Use
3. Specifications

1. DATA AND DOCUMENTATION

Code	Description	Dimensions (mm)	Weight	Pkg. / Pallet
TER30-7044	ABS inspection door	165 x 165	0.084 kg/pc.	6 pcs. / 720 pcs.
TER30-7045	ABS inspection door	165 x 215	0.090 kg/pc.	6 pcs. / 450 pcs.
TER30-7046	ABS inspection door	215 x 215	0.095 kg/pc.	6 pcs. / 450 pcs.
TER30-7047	ABS inspection door	215 x 265	0.100 kg/pc.	6 pcs. / 300 pcs.
TER30-7048	ABS inspection door	215 x 315	0.115 kg/pc.	6 pcs. / 300 pcs.
TER30-7049	ABS inspection door	305 x 305	0.120 kg/pc.	6 pcs. / 204 pcs.

MATERIAL

Made of glossy white ABS, it is particularly resistant to weathering.

2. USE

It allows for quick and easy inspection of the space behind.

3. SPECIFICATION ITEMS

Entry	Description	Unit	Price
Dak.O.TER30.704x	Supply and installation of an inspection hatch consisting of a support frame and a door with a rounded profile. Can be opened and closed by push. Individually shrink-wrapped with barcode. Made of glossy white ABS, it is particularly resistant to weathering. It allows for quick and easy inspection of the space behind.		
Dak.O.TER30.7044	Dimensions 165 x 165 mm.....	pc.	-
Dak.O.TER30.7045	Dimensions 165 x 215 mm.....	pc.	-
Dak.O.TER30.7046	Dimensions 215 x 215 mm.....	pc.	-
Dak.O.TER30.7047	Dimensions 215 x 265 mm.....	pc.	-
Dak.O.TER30.7048	Dimensions 215 x 315 mm.....	pc.	-
Dak.O.TER30.7049	Dimensions 305 x 305 mm.....	pc.	-