

# VALVE WITH SPRING AND ADJUSTABLE DIFFUSER



## INDEX

1. Data and Documentation
2. Use
3. Specifications

## 1. DATA AND DOCUMENTATION

Code	Description	Dimensions (mm)	Weight	Pkg. / Pallet
TER30-7165	Fixed Valve with Adjustable Diffuser Spring without ABS Mesh	ø 100	0.090 kg/pc.	10 pcs. / 500 pcs.
TER30-7166	Fixed Valve with Adjustable Diffuser Spring without ABS Mesh	ø 125	0.130 kg/pc.	10 pcs. / 340 pcs.
TER30-7167	Fixed Valve with Adjustable Diffuser Spring without ABS Mesh	ø 150/160	0.170 kg/pc.	10 pcs. / 340 pcs.

### MATERIAL

Made of matt white-effect ABS, it is particularly resistant to weathering.

## 2. USE

It promotes air recirculation between indoor and outdoor spaces and room ventilation, limiting condensation and mould formation. Using the spring adjustment system, it can adapt to different diameters.

## 3. SPECIFICATION ITEMS

Entry	Description	Unit	Price
<b>Dak.O.TER30.716x</b>	Supply and installation of a spring-loaded valve with adjustable diffuser made of matt white. Individually shrink-wrapped with barcode. Made of matt white ABS, it is particularly resistant to ageing due to exposure to atmospheric agents. It favours the recirculation of air between indoors and outdoors and the ventilation of rooms, limiting condensation and the formation of mould. Using the spring adjustment system, it can adapt to different diameters.		
<b>Dak.O.TER30.7165</b>	ø 100 mm.....	pc.	-
<b>Dak.O.TER30.7166</b>	ø 125 mm.....	pc.	-
<b>Dak.O.TER30.7167</b>	ø 150/160 mm.....	pc.	-