

ANCIENS FONDS - READY-TO-USE PUTTY



INDEX

1. Data and Documentation
2. Laying
3. Precautions for use
4. Consumption and drying
5. Specifications

1. DATA AND DOCUMENTATION

Code	Description	Dimensions (mm)	Colour	Packaging	Pkg / Pallet
TER15-1872	Anciens Fonds - Ready-to-use putty - 1.5 kg	1.5 kg	White	16 pcs.	256 pcs.
TER15-1873	Anciens Fonds - Ready-to-use putty - 5 kg	5 kg	White	1 pc.	54 pcs.

MATERIAL

Made from emulsion resin, calcium carbonate, water and various additives. Off-white colour.

USE

SEMIN ANCIENS FONDS is a ready-mixed, ready-mixed putty for irregular levelling on interior and exterior walls, suitable for renovation and restoration of any uneven or damaged substrate/support. Thanks to its formulation based on perfectly water-resistant resins, it is particularly suitable for wet rooms (kitchens, bathrooms, technical rooms).

TECHNICAL FEATURES

Grain size: up to 0.6 mm. Adhesion: in accordance with NFT 30 608. pH: neutral. Dry extract: 80%.

PERMISSIBLE MEDIA

Terracotta blocks, Plasterboard, Cement plaster, Old paint, Sanded wood, Plaster, Concrete, Fibreglass.



ANCIENS FONDS - READY-TO-USE PUTTY

2. INSTALLATION

SURFACE PREPARATION

Substrates must be clean, dry, hard and free of dust and any traces of formwork release oil. APPLICATION: Application is carried out with a sander or spatula.

APPLICATION THICKNESS: up to 5 mm in one coat

3. PRECAUTIONS FOR USE

The application and drying temperature must be between 5°C and 35°C. Do not apply on damp substrates

4. CONSUMPTION AND DRYING

CONSUMPTION: Thickness approx. 1.5 kg / m² / mm.

DRYING TIME: Depends on weather conditions, type of substrate and thickness of application.. As a general rule, for 5 mm thickness SEMIN AN-CIENS FONDS dries between 24 and 36 hours.

5. SPECIFICATION ITEMS

Entry	Description	Unit	Price
Dak.D.TER15.1872	Supply and installation of SEMIN ACIENS FONDS Ready-to-use grout Available in off-white. Made from emulsion resin, calcium carbonate, water and various additives Used for tiling uneven indoor/outdoor surfaces. Thanks to its formulation based on water-resistant resins, it is particularly suitable for wet rooms (kitchens, bathrooms, technical rooms).	pc.	-
Dak.D.TER15.1872	1.5 kg.....	pc.	-
Dak.D.TER15.1873	5 kg.....	pc.	-

