

# ALULIGHT HYDRO



	a (nom)	b (nom)	c	
<b>6040</b>	200	200	12,5	mm
<b>6041</b>	300	300	12,5	mm
<b>6042</b>	400	400	12,5	mm
<b>6043</b>	450	450	12,5	mm
<b>6044</b>	500	500	12,5	mm

## INDEX

1. Data and Documentation
2. Use
3. Specification item

## 1. DATA AND DOCUMENTATION

Code	Description	Dimensions (mm)	Pkg.	Pallet	Weight
GAN01-6040	AluLight with Hydro Panel	200 x 200	1 pc.	243 pcs.	710 g/pcs.
GAN01-6041	AluLight with Hydro Panel	300 x 300	1 pc.	120 pcs.	1,250 g/pc.
GAN01-6042	AluLight with Hydro Panel	400 x 400	1 pc.	55 pcs.	1,900 g/pc.
GAN01-6043	AluLight with Hydro Panel	500 x 500	1 pc.	45 pcs.	2,740 g/pc.
GAN01-6044	AluLight with Hydro Panel	600 x 600	1 pc.	32 pcs.	3,760 g/pcs.

## 2. USE

Used for ceilings, walls and counter walls.

## 3. SPECIFICATION ITEMS

Entry	Description	Unit	Price
<b>Dak.B.GAN01.604x</b>	Supply and installation of inspection hatch with Hydro panel (suitable for wet rooms). Completely detachable panel with "anti-fall" device and concealed snap closure. Hatch not fitted with lip seal. Patented mechanical fixing of plasterboard. Available in 12.5 mm thick versions. Individually boxed. Aluminium frame, water-resistant Hydro plasterboard with fixing. Used for false ceilings, walls and counter walls. Delivered to the construction site in a cardboard box with a label showing the product characteristics.		
<b>Dak.B.GAN01.6040</b>	Dimensions 200 x 200 mm - thickness 12.5 mm.....	pc.	-
<b>Dak.B.GAN01.6041</b>	Dimensions 300 x 300 mm - thickness 12.5 mm.....	pc.	-
<b>Dak.B.GAN01.6042</b>	Dimensions 400 x 400 mm - thickness 12.5 mm.....	pc.	-
<b>Dak.B.GAN01.6043</b>	Dimensions 500 x 500 mm - thickness 12.5 mm.....	pc.	-
<b>Dak.B.GAN01.6044</b>	Dimensions 600 x 600 mm - thickness 12.5 mm.....	pc.	-