

# DOUBLE-SIDED SEALING TAPE



## INDEX

1. Data and Documentation
2. Use
3. Specifications

## 1. DATA AND DOCUMENTATION

Code	Description	Measures	Weight	Colour	Pkg. / Pallet
RET23-5305	Double-sided PE Foam Gasket Tape for Plasterboard	45 mm x 30 m	0.05 kg/pc.	-	20 pcs. / - pcs.
RET23-5306	PE Foam Gasket Double-Sided Tape for Plasterboard	65 mm x 30 m	0.06 kg/pc.	-	14 pcs. / - pcs.
RET23-5307	PE Foam Gasket Double-Sided Tape for Plasterboard	90 mm x 30 m	0.07 kg/pc.	-	10 pcs. / - pcs.

### MATERIAL

Made of waterproof, closed-cell, cross-linked polyethylene foam.

## 2. USE

Used as a sealing adhesive jointing element to join plasterboard walls and flooring.

## 3. SPECIFICATION ITEM

Entry	Description	U.M.	Price
<b>Dak.B.RET23.530x</b>	Supply and installation of sealing tape with density 33 kg/m3. Thickness 3 mm. Dimensions 45 / 65 / 90 mm x 30 m. Packed in boxes. Made of waterproof, closed-cell, cross-linked polyethylene foam. Used as a sealing adhesive jointing element to join plasterboard walls and flooring.		
<b>Dak.B.RET23.5305</b>	Dimensions 45 mm x 30 m.....	pc.	-
<b>Dak.B.RET23.5306</b>	Dimensions 65 mm x 30 m.....	pc.	-
<b>Dak.B.RET23.5307</b>	Dimensions 90 mm x 30 m.....	pc.	-