

SINGLE-SIDED SEALING TAPE



INDEX

1. Data and Documentation
2. Use
3. Specifications

1. DATA AND DOCUMENTATION

Code	Description	Measures	Weight	Colour	Pkg. / Pallet
RET23-5300	PE Foam Gasket Tape for Plasterboard	30 mm x 30 m	0.040 kg/pc.	-	30 pcs. / - pcs.
RET23-5301	PE Foam Gasket Tape for Plasterboard	45 mm x 30 m	0.045 kg/pc.	-	20 pcs. / - pcs.
RET23-5302	PE Foam Gasket Tape for Plasterboard	65 mm x 30 m	0.050 kg/pc.	-	14 pcs. / - pcs.
RET23-5303	PE Foam Gasket Tape for Plasterboard	90 mm x 30 m	0.060 kg/pc.	-	10 pcs. / - pcs.

MATERIAL Made of waterproof, closed-cell, cross-linked polyethylene foam.

2. USE

Used as a sealing adhesive jointing element to join plasterboard walls and flooring.

3. SPECIFICATION ITEM

Entry	Description	U.M.	Price
Dak.B.RET23.530x	Supply and installation of sealing tape with density 33 kg/m3. Thickness 3 mm. Dimensions 30 / 45 / 65 / 90 mm x 30 m. Packed in boxes. Made of closed-cell waterproof cross-linked polyethylene foam. Used as an adhesive sealing joint element to be applied below/above the partition wall rail.		
Dak.B.RET23.5300	Dimensions 30 mm x 30 m.....	pc.	-
Dak.B.RET23.5301	Dimensions 45 mm x 30 m.....	pc.	-
Dak.B.RET23.5302	Dimensions 65 mm x 30 m.....	pc.	-
Dak.B.RET23.5303	Dimensions 90 mm x 30 m.....	pc.	-