

OSCAR - PREMIXED PUTTY



INDEX

1. Data and Documentation
2. Laying
3. Precautions for use
4. Consumption and drying
5. Specifications

1. DATA AND DOCUMENTATION

Code	Description	Dimensions (mm)	Colour	Packaging	Pkg / Pallet
TER15-1874	Oscar - Premixed Putty - 1.5 kg	1.5 kg	White	16 pcs.	256 pcs.
TER15-1875	Oscar - Premixed Putty - 5 kg	5 kg	White	1 pc.	88 pcs.

MATERIAL

Made from emulsion resin, calcium carbonate, water and various additives. Colour white.

USE

SEMIN OSCAR is a paste filler for interior and exterior finishing work on walls and ceilings. Substrates prepared with OSCAR will be ready to receive high-end finishing paints (matt, satin or gloss). Due to the high resin content in its composition, OSCAR will be relatively waterproof after complete drying, thus saving paint. Its formulation also makes it suitable for humid environments.

TECHNICAL FEATURES

Density of the mixture: 1.9.
Grain size: very fine. pH: 7.
Adhesion: in accordance with NFT 30 608

PERMISSIBLE MEDIA

INTERIOR WALLS AND CEILINGS:
Plasterboard, Concrete, Old paint, Sanded and painted wood, Gypsum tiles, Cement plaster, Gypsum-based roughcast plaster
EXTERNAL WALLS:
Smooth cement, Fine floating cement



OSCAR - PREMIXED PUTTY

2. INSTALLATION

SURFACE PREPARATION BEFORE LAYING.

Interior substrates must comply with DTU 59.1, i.e. clean, dry, dust-free, hard and free of any traces of separating agent. On excessively uneven substrates, apply a degreasing plaster beforehand.

Sand, brush and dust concrete, plasterboard and tiles. Wash, rinse and primer old paintwork.

APPLICATION.

Application is done manually with a smoothing tool or spatula. The maximum thickness will be 1 mm per layer. Peel and sand if necessary before the plaster is completely dry. Tools are simply cleaned with water.

3. PRECAUTIONS FOR USE

The temperature during application and during drying must be between 8 and 35°C.

Outdoors, it must be covered. Do not apply on plastic covers. Do not add antifreeze, oil or solvents

4. CONSUMPTION AND DRYING

CONSUMPTION: Approx. 250gr/m².

DRYING TIME: Approx. 4 to 8 hours depending on thickness, substrate and environmental conditions.

5. SPECIFICATION ITEMS

Entry	Description	Unit	Price
Dak.D.TER15.1874	Supply and application of SEMIN OSCAR premixed grout made of resin emulsion, calcium carbonate, water and various additives. Colour white. SEMIN OSCAR is a paste filler for interior and exterior finishing work on walls and ceilings. Substrates prepared with OSCAR will be ready to receive high-end finishing paints (matt, satin or gloss). Due to the high resin content in its composition, OSCAR will, after complete drying, be relatively waterproof and thus save paint. Its formulation also makes it suitable for humid environments. Supplied in 1.5 kg bucket.....	pc.	-
Dak.D.TER15.1875	Supply and application of SEMIN OSCAR premixed grout made of resin emulsion, calcium carbonate, water and various additives. Colour white. SEMIN OSCAR is a paste filler for interior and exterior finishing work on walls and ceilings. Substrates prepared with OSCAR will be ready to receive high-end finishing paints (matt, satin or gloss). Due to the high resin content in its composition, OSCAR will, after complete drying, be relatively waterproof and thus save paint. Its formulation also makes it suitable for humid environments. Supplied in 5 kg bucket.....	pc.	-

