

RE-BOUCH-TROU - SPRAY PUTTY



INDEX

1. Data and Documentation
2. Laying
3. Precautions for use
4. Drying time
5. Specifications

1. DATA AND DOCUMENTATION

Code	Description	Dimensions (mm)	Colour	Packaging	Pkg / Pallet
TER15-1876	Re-Bouch-Trou - Spray Putty - 125 ml	125 ml	White	12 pcs.	840 pcs.

MATERIAL

Made from emulsion resin and various additives. Colour white.

USE

A filler for interior use, Re-Bouch-Trou can repair small cracks and screw holes. Available as a spray, the product fills a hole in a blank wall in just a few sprays. The paste obtained after application of the putty is snow-white in colour and can be smoothed simply by means of the spatula integrated in the spray cap.

TECHNICAL FEATURES

Density of the mixture: 0.4 g/m³.
pH: 7.

PERMISSIBLE MEDIA

WALLS AND INTERIORS:
The ready-to-use filler is easy to use thanks to its aerosol format. It is ideal for various types of interior wall substrates: plaster, plasterboard, masonry, plaster, cellular concrete, concrete and cement plaster.

RE-BOUCH-TROU - SPRAY PUTTY

2. INSTALLATION

A few steps must be followed so that the plaster fills the hole in a white wall without difficulty.

- Shake the ready putty for 2 minutes until the ball comes loose;
- Hold the can upright, head up, and spray on a piece of cardboard (test);
- Insert the straw into the hole or slot to be filled;
- Spray into the hole until full (bottom up in case of cracks);
- Smooth with the spatula integrated in the cap;
- Rinse the straw well with warm water;
- If necessary, perform a second step on the following day.

3. PRECAUTIONS FOR USE

The temperature during application and during drying must be between 8 and 35 °C. Caution: pressurised container, may explode due to heat

4. DRYING TIME

DRYING TIME: Maximum 4 hours, depending on substrate and environmental conditions.

5. SPECIFICATION ITEMS

Entry	Description	Unit	Price
Dak.D.TER15.1876	Supply and installation of SEMIN RE-BOUCH-TROU spray filler Available in white. Made from emulsion resins and various additives. Used to cover screw holes, small holes and/or cracks. Supplied in 125m spray canl.....	pc.	-