DAKOTA TECHNICAL DATA SHEET

REBOUCHER PRO - POWDERED WALL FILLER



INDEX

- 1. Data and Documentation
- 2. Laying
- 3. Precautions for use
- 4. Consumption and drying
- 5. Specifications

1. DATA AND DOCUMENTATION

Code	Description	Dimensions (mm)	Colour	Packaging	Pkg / Pallet
TER15-1883	Reboucher Pro - Interior wall filler powder - 5 kg	5 kg	White	1 pc.	160 pcs.

MATERIAL	Made from gypsum-based powder, calcium carbonate, mineral fillers and various additives.		
USE	Putty for INTERNAL use, in powder form for filling cracks, holes and cuts of all sizes. Also for sealing and repairing.		
TECHNICAL FEATURES	pH: neutral. Setting time: 30 minutes depending on ambient conditions and applied thickness. Adhesion: complies with NF T 30 608		
PERMISSIB LE MEDIA	All types of unpainted or painted interior substrates: plaster, plasterboard, gypsum tiles, concrete, cement plaster, agglomerates, cellular concrete, bricks, terracotta, etc. The finish, after complete drying of the filler, can be executed with all types of paints, gypsum-based coatings, pasty coatings, varnished paper glue.		



р. 1 /2

DAKOTA TECHNICAL DATA SHEET

REBOUCHER PRO - POWDERED WALL FILLER

2. INSTALLATION

SURFACE PREPARATION Application surfaces must be clean, dry, sound, hard and free of dust and any traces of oil. Open the slots correctly. MIX PROPORTIONS Usually about 2 parts Reboucher Pro filler to 1 part water. Ideal mix: • 2.75 litres of water per 5 kg bag. APPLICATION. Application is performed with a spatula.

3. PRECAUTIONS FOR USE

The temperature during application and during drying must be between 8 and 35°C. Do not apply on a damp surface. Do not use filler that has already begun to harden.

4. CONSUMPTION AND DRYING

CONSUMPTION: 1 kg / m² / mm thickness.

DRYING TIME. It depends on the environmental conditions, the type of substrate and the thickness of application. As a general rule, for 1 cm thickness, the putty will dry in 6 hours.

5. SPECIFICATION ITEMS

Entry	Description	Unit	Price
Dak.D.TER15.1887	Supply and application of powdered wall putty. SEMIN REBOUCHER PRO. Available in white. Made from gypsum-based powder, calcium carbonate, mineral fillers and various additives. Reboucher Pro is designed for indoor use to quickly fill cracks, holes and cuts of all sizes without shrinkage o		-

