

SECUTECNA EI120




INDEX

1. Data and Documentation
2. Use
3. Specification item

1. DATA AND DOCUMENTATION

Code	Description	Dimensions (mm)	Pkg.	Pallet	Weight
GAN01-6441	Secutecna F120/EI120 with Key Locking	300 x 300	1 pc.	12 pcs.	8,80 Kg/pz.
GAN01-6443	Secutecna F120/EI120 with Key Locking	400 x 400	1 pc.	8 pcs.	14,02 Kg/pz.
GAN01-6445	Secutecna F120/EI120 with Key Locking	500 x 500	1 pc.	7 pcs.	20,52 Kg/pz.
GAN01-6446	Secutecna F120/EI120 with Key Locking	600 x 600	1 pc.	5 pcs.	28,16 Kg/pz.
GAN01-6448	Secutecna F120/EI120 with Key Locking	800 x 800	1 pc.	5 pcs.	46,76 Kg/pz.

CERTIFICATION



Fire resistance class EI120 Tested according to CZ EN 4102-02

2. USE

Utilizzata in controsoffitti autonomi con protezione antincendio EI120 (E = attitudine a non lasciar passare né produrre fiamme, vapori o gas caldi sul lato non esposto; I = attitudine a ridurre la trasmissione del calore.)

3. SPECIFICATION ITEMS

Entry	Description	Unit	Price
Dak.B.GAN01.644x	Supply and installation of 120-minute fire resistant inspection hatch (EI120) with built-in fire protection (patented) and lockable. 2 x 25 mm fireproof plasterboard lining and intumescent protection. Individually boxed. Aluminium frame, fire-resistant plasterboard panel. Utilizzata in controsoffitti autonomi con protezione antincendio EI120 (E = attitudine a non lasciar passare né produrre fiamme, vapori o gas caldi sul lato non esposto; I = attitudine a ridurre la trasmissione del calore.) Delivered to the construction site in a cardboard box with a label showing the product characteristics.		
Dak.B.GAN01.6441	Dimensions 300 x 300 mm - EI120 - thickness 2 x 25 mm.....	pc.	-
Dak.B.GAN01.6443	Dimensions 400 x 400 mm - EI120 - thickness 2 x 25 mm.....	pc.	-
Dak.B.GAN01.6445	Dimensions 500 x 500 mm - EI120 - thickness 2 x 25 mm.....	pc.	-
Dak.B.GAN01.6446	Dimensions 600 x 600 mm - EI120 - thickness 2 x 25 mm.....	pc.	-
Dak.B.GAN01.6448	Dimensions 800 x 800 mm - EI120 - thickness 2 x 25 mm.....	pc.	-