

CAMBERED HEAD POLYAMIDE IMPACT PLUG



INDEX

- 1. Data and Documentation
- 2. Use
- 3. Specifications

1. DATA AND DOCUMENTATION

Code	Description	Dimensions (mm)	Weight	Colour	Pkg. / Pallet
MIN01-5226	Polyamide Percussion Dowel with Domed Head	ø 6 x 35	0.444 kg/cf.	Grey	100 pcs / 57,600 pcs
MIN01-5227	Polyamide Percussion Dowel with Domed Head	ø 6 x 40	0.444 kg/cf.	Grey	100 pcs. / 86,400 pcs.
MIN01-5228	Polyamide Percussion Dowel with Domed Head	ø 6 x 55	0.472 kg/cf.	Grey	100 pcs / 57,600 pcs
MIN01-5229	Polyamide Percussion Dowel with Domed Head	ø 6 x 60	0.583 kg/cf.	Grey	100 pcs. / 38,400 pcs.

MATERIAL

Made of polyamide and steel screw.

2. USE

Used for fixing on solid masonry and ceilings.

3. SPECIFICATION ITEMS

Entry	Description	Unit	Price
Supply and installation of Percussion Dowel with Domed Head ø 6 x 35 / 40 / 55 / 60 mm. Packed in boxes of 100 pieces. Made of polyamide and steel screw. Used for fixing on solid masonry and ceilings.			
Dak.B.MIN01.5226	ø 6 x 35 mm	cf.	-
Dak.B.MIN01.5227	ø 6 x 40 mm	cf.	-
Dak.B.MIN01.5228	ø 6 x 55 mm.	cf.	-
Dak.B.MIN01.5229	ø 6 x 60 mm.	cf.	-



