

COUNTERSUNK SCREW DRILL BIT FOR OUTSIDE



INDEX

1. Data and Documentation
2. Use
3. Specifications

1. DATA AND DOCUMENTATION

Code	Description	Dimensions (mm)	Weight	Colour	Pkg. / Pallet
MIN02-42025	Countersunk Head Drill Bolt for external use	ø 4.2 x 25	1.15 kg/cf.	Grey	500 pcs. / 10 cf.
MIN02-42032	Countersunk Head Drill Bolt for external use	ø 4.2 x 32	1.15 kg/cf.	Grey	500 pcs. / 10 cf.
MIN02-42038	Countersunk Head Drill Bolt for external use	ø 4.2 x 38	1.00 kg/pf.	Grey	250 pcs. / 10 cf.
MIN02-42045	Countersunk Head Drill Bolt for external use	ø 4.2 x 45	1.00 kg/pf.	Grey	250 pcs. / 10 cf.

MATERIAL Made of case-hardened steel, special finish.

2. USE

Use in outdoor areas, with high corrosion resistance in salt spray (over 1,000 hours) also allows use in open spaces.

3. SPECIFICATION ITEMS

Entry	Description	Unit	Price
Dak.B.MIN01.420xx	Supply and installation of Screws for fixing fibre cement, plasterboard and similar panels to metal structures. Flat countersunk head with self-drilling flange, H-type cross impression, case-hardened steel, special finish with high resistance to salt spray (over 1,000 hours). No pre-drilling required for metal substrate thicknesses up to max. 3 mm (min. 0.8 mm). Made of case-hardened steel, special finish. Use in outdoor areas, with high resistance to corrosion in salt spray allows it to be used outdoors.		
Dak.B.MIN01.42025	ø 4.2 x 25 mm.....	cf.	-
Dak.B.MIN01.42032	ø 4.2 x 32 mm.....	cf.	-
Dak.B.MIN01.42038	ø 4.2 x 38 mm.....	cf.	-
Dak.B.MIN01.42045	ø 4.2 x 45 mm.....	cf.	-