

# DK PLASTER S-VEIL



## INDEX

1. Code Registry
2. Use
3. Technical Specification

## 1. CODE REGISTRY

Code	Product Description	Dimensions (m)	Weight	Colour	Pkg. / Pallet
RET03-VEL240	Dk Plaster S-Veil	1,00 x 15 m	45 gr./m <sup>2</sup>	White	15 m <sup>2</sup> / 1.440 m <sup>2</sup>

**MATERIAL** Made of fiber glass Adfors Saint-Gobain.

Characteristics	Units Description	RET03-VEL240	
		Warp	Weft
<b>Tensile strenght</b>	N/2,45 cm	75 N	43 N
<b>Standard height</b>	cm	100	
<b>Roll length</b>	m	15	
<b>Treated Fabric Thickness</b>	mm	0,39 ± 4	
<b>Loom state Fabric Weight</b>	g/m <sup>2</sup>	45 ± 4	
<b>LOI</b>	%	18 - 22	

Tolerances:

Height: ± 1%  
Length: ± 2%  
LOI: ± 3%

Packing:

The rolls of fabrics are packed vertically in a cardboard box, on a wooden pallet.

Storing:

Packed rolls are to be stored in dry rooms. Storing temperature is from -10 °C to +50°C.

## 2. USE

Used on interior walls or drywall, to smooth irregularities and give stability to plaster and plasterboard compounds or to additionally restore damaged plaster or finishing panels.

## 3. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
<b>Dak.B.RET03.VEL240</b>	Supply and installation of White fiber glass mesh recommended for leveling of irregular surfaces, covering the roughness of walls and ceilings ensuring a smooth and better finishing. The veil of fiber glass increases the toughness and stability of plaster and drywall, as it has been designed to create an excellent compound between different materials. Size: height 1,00 x 15 m. Made of ber glass Adfors Saint-Gobain. Used on interior walls or drywall, to smooth irregularities and give stability to plaster and plasterboard compounds or to additionally restore damaged plaster or finishing panels.	m <sup>2</sup>	-