

GALVANIZED SCREW FOR WOOD PANEL



INDEX

1. Code Registry
2. Use
3. Technical specification

1. CODE REGISTRY

Code	Description	Dimensions (mm)	Weight	Colour	Pkg. / Pallet
TER11-2240L5	Galvanized screw for wood panel	50 x ø 5	4 gr./pc.	Galvanized	200 pcs. / - pc.
TER11-2240L6	Galvanized screw for wood panel	60 x ø 5	4 gr./pc.	Galvanized	200 pcs. / - pc.
TER11-2240L7	Galvanized screw for wood panel	70 x ø 5	4 gr./pc.	Galvanized	200 pcs. / - pc.
TER11-2240L8	Galvanized screw for wood panel	80 x ø 5	4 gr./pc.	Galvanized	200 pcs. / - pc.
TER11-2240L9	Galvanized screw for wood panel	90 x ø 5	4 gr./pc.	Galvanized	200 pcs. / - pc.
TER11-2240L10	Galvanized screw for wood panel	100 x ø 5	10 gr./pc.	Galvanized	100 pcs. / - pc.
TER11-2240L12	Galvanized screw for wood panel	120 x ø 6	10 gr./pc.	Galvanized	100 pcs. / - pc.
TER11-2240L14	Galvanized screw for wood panel	140 x ø 6	10 gr./pc.	Galvanized	100 pcs. / - pc.
TER11-2240L16	Galvanized screw for wood panel	160 x ø 6	10 gr./pc.	Galvanized	100 pcs. / - pc.
TER11-2240L18	Galvanized screw for wood panel	180 x ø 6	10 gr./pc.	Galvanized	100 pcs. / - pc.
TER11-2240L20	Galvanized screw for wood panel	200 x ø 6	10 gr./pc.	Galvanized	100 pcs. / - pc.

MATERIAL Made of galvanized steel.

2. USE

Used for mechanical anchoring of insulating boards to wood support (dry system), supporting the load and tensile "tear-off" stress.

3. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
Dak.B.TER11.2240Lx	Supply and installation of washer anchor for fixing the insulating boards to wood support. Made of galvanized steel. Used for mechanical anchoring of insulating boards to wood support (dry system), supporting the load and tensile "tear-off" stress.		
Dak.B.TER11.2240L5	Lenght 50 mm - ø 5 mm.....	pc.	-
Dak.B.TER11.2240L6	Lenght 60 mm - ø 5 mm.....	pc.	-
Dak.B.TER11.2240L7	Lenght 70 mm - ø 5 mm.....	pc.	-
Dak.B.TER11.2240L8	Lenght 80 mm - ø 5 mm.....	pc.	-
Dak.B.TER11.2240L9	Lenght 90 mm - ø 5 mm.....	pc.	-
Dak.B.TER11.2240L10	Lenght 100 mm - ø 5 mm.....	pc.	-
Dak.B.TER11.2240L12	Lenght 120 mm - ø 6 mm.....	pc.	-
Dak.B.TER11.2240L14	Lenght 140 mm - ø 6 mm.....	pc.	-
Dak.B.TER11.2240L16	Lenght 160 mm - ø 6 mm.....	pc.	-
Dak.B.TER11.2240L18	Lenght 180 mm - ø 6 mm.....	pc.	-
Dak.B.TER11.2240L20	Lenght 200 mm - ø 6 mm.....	pc.	-