


ROUND SPACER FOR FORMWORK



Codice	h.
PRO12-1658	10 mm
PRO12-1658B	15 mm
PRO12-1659	20 mm
PRO12-1659B	25 mm
PRO12-1657	30 mm
PRO12-1657B	40 mm



INDEX

1. Code Registry
2. Use
3. Technical Specification

1. CODE REGISTRY

Code	Description	Dimension (mm)	Weight	Pkg. / Pallet
PRO12-1658	Round spacer for formwork	h thick. 10	2 gr/pcs.	2.000 pcs. / 100.000 pcs.
PRO12-1658B	Round spacer for formwork	h thick. 15	4 gr/pcs.	1.000 pcs. / 50.000 pcs.
PRO12-1659	Round spacer for formwork	h thick. 20	4 gr/pcs.	1.000 pcs. / 30.000 pcs.
PRO12-1659B	Round spacer for formwork	h thick. 25	5 gr/pcs.	1.000 pcs. / 20.000 pcs.
PRO12-1657	Round spacer for formwork	h thick. 30	5 gr/pcs.	1.000 pcs. / 20.000 pcs.
PRO12-1657B	Round spacer for formwork	h thick. 40	6 gr/pcs.	500 pcs. / 22.500 pcs.

MATERIAL Made of thermoset plastic.

2. USE

Specific use in construction.
It allows the installation of rebar, maintaining the correct distance for the "concrete cover".

3. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
Dak.O.PRO12.165x	Supply and installation of spacer for round shape allows the installation of reinforcement cages. Packed in box. Made of thermoset plastic. Specific use in construction. It allows the installation of rebar, maintaining the correct distance for the "concrete cover".		
Dak.O.PRO12.1658	h thickness 10 mm.....	pcs	-
Dak.O.PRO12.1658B	h thickness 15 mm.....	pcs	-
Dak.O.PRO12.1659	h thickness 20 mm.....	pcs	-
Dak.O.PRO12.1659B	h thickness 25 mm.....	pcs	-
Dak.O.PRO12.1657	h thickness 30 mm.....	pcs	-
Dak.O.PRO12.1657B	h thickness 40 mm.....	pcs	-